

Package: wget (via r-universe)

September 4, 2024

Title Setting Download Method to 'wget'

Version 0.0.2

Description Provides function, `wget_set()`, to change the method (default to 'wget -c') using in `download.file()`. Using 'wget -c' allowing continued downloading, which is especially useful for slow internet connection and for downloading large files. User can run `wget_unset()` to restore previous setting.

Imports yulab.utils (>= 0.1.7)

License Artistic-2.0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

NeedsCompilation no

Repository <https://yulab-smu.r-universe.dev>

RemoteUrl <https://github.com/yulab-smu/wget>

RemoteRef HEAD

RemoteSha 92d4c7a67801c648642c8d563229f2f37d57c1e1

Contents

wget_set	2
wget_unset	2

Index	4
--------------	----------

*wget_set**wget_set*

Description

set "download.file.method" to "wget" and "download.file.extra" to "-c"

Usage

```
wget_set(method = "wget", extra = "-c")
```

Arguments

method	download method (wget, default)
extra	extra parameter (-c, default)

Details

setting download method to "wget -c", so that it can continue the download from where it left off.

Value

No return value, called for side effects

Author(s)

Guangchuang Yu

Examples

```
wget_set()
```

*wget_unset**wget_unset*

Description

unset download method setting by wget_set

Usage

```
wget_unset()
```

Details

set the download method and extra parameter back to what it is or NULL if it is not specify

Value

No return value, called for side effects

Author(s)

Guangchuang Yu

Examples

`wget_unset()`

Index

wget_set, 2
wget_unset, 2